

INDEX

Pneumatic Press Options	2-3	Manual Press Attachments	14
Pneumatic Presses	4-10	Die Sets	16-18
Manual Presses	11-15	Die Sets Components	19

Specifications subject to change without prior notice.

LASTING IMPRESSIONS

The quality of materials and workmanship means you'll have your JT&M press for a very long time. Many of our original presses are still in service after forty years.

24-HOUR SHIPPING

JT&M will ship your order within 24 hours of its receipt. This is accomplished by keeping a sufficient inventory of presses and their component parts in stock at all times. JT&M products can be ordered, assembled, and shipped the very same day!

PRESSING PRODUCTS

The rest of this catalog is devoted to our presses and die sets. The first section profiles our pneumatic-powered presses, followed by our manual presses and die sets. We're anxious to help you select the right press for your needs. Call us with your questions at **(608) 868-4711**.

512 & Model 544 Filter/Regulators Recommended for use on all pneumatic presses to remove moisture and dirt, and to allow the user accurate supply pressure.

- **Model 512** – used for A-1000 series thru A-3000 and A-6000 series presses, comes standard with a 1/4" N.P.T. pipe fitting.
- **Model 544** – used for A-4000 and A-5000 series presses, comes standard with a 1/2" N.P.T. pipe fitting.

Model 750 220 v Transformer Kit 240 v to 120 v-50/60 Hz

Air/Oil Systems can reduce break through surge as well as provide the smoothness and rigidity of a hydraulic system without the inherent high costs and space consuming components needed to operate the press. (Add suffix A/O to the end of the model # when ordering.)

The Tool Adapter Designed for easy assembly and disassembly of JT&M's mini die sets. The tool adapter threads into the ram of the cylinder with either a 1/2-13 thread for 1 3/4" and 3" bore or a 3/4-10 thread for the 4 1/2" bore and multistage cylinder. Choice of lengths include 1 1/2", 2 1/2", 3 1/2", or 4 1/2". This accessory is identified by TA 1/2 - length for 1/2-13 thread or TA 3/4 - length for 3/4-10 thread.



Model 512



Air/Oil

Example:

TA 1/2 - 4 1/2" (1/2-13 thread by 4 1/2" lg.)



Tool Adapter