

The A-3000 series air press allows the user height adjustment of the cylinder in 1.875" increments. This press is ideal for assembly, punching, shearing, and staking of metal or plastic. Upon special request, the column height can be increased by adding a riser block between the base and the column. The A-3000 series pneumatic press comes equipped with dual hand anti-tie-down/anti-repeat controls and a three-inch stroke length. An optional adjustable down stop/anti-rotate mechanism is available.

Options:

- Tool Adapters
- Air Filter/Regulator (Model 512)
- Die Sets (See Page 16)
- Alternate Stroke Lengths
- Arrange Press For Die Set Mtg.
Add Suffix (-A)
- Riser Blocks
- Quick Exhaust Valves (Model 523)
- Delay Timer (Model T-10A)
- Dual Photo Optic Palm Buttons
Add Suffix (-OT)
- Air Over Oil
Add Suffix (-A/O)



Model	A	B	CYL. DIA.	Force at 60 PSI	Force at 80 PSI	Force at 100 PSI
A-3070	20.38	.25	3.00"	420	560	700
A-3160	20.38	.25	4.50"	960	1280	1600
A-3243	23.38	.66	4.00"	1458	1944	2430
*A-3066	23.75	.25	3.00"	396	528	660
*A-3151	23.75	.25	4.50"	906	1208	1510
*A-3235	28.38	.66	4.00"	1400	1880	2350

*Includes adjustable down stop/anti-rotate mechanism.

