

A-5000 series pneumatic press consists of a precision machined four-post casting that incorporates a multistage cylinder, allowing the user a force up to 6120 pounds. Dual hand photo-optic anti-tie down/anti-repeat controls come standard. The control box is separate and may be mounted in front of the press or on the side of a table. The A-5000 comes standard with a three-inch stroke. Alternate stroke lengths are available upon request.

Options:

- Die Sets (See Page 16)
- Arrange Press For Die Set Mtg.
Add suffix (-A)
- Tool Adapters
- Air Filter/Regulator (Model 544)
- Longer Post Lengths
- Alternate Stroke Lengths
- Quick Exhaust Valves (Model 523)
- Delay Timer (Model T-10B)
- Power Die Sets (See Page 18)
- Air Over Oil
Add Suffix (-A/O)



Model: A-5310, A-5461, A-5612



Model: *A-5302, *A-5453, *A-5604

| Model | Force at 60 PSI | Force at 80 PSI | Force at 100 PSI |
|-------------------------|-----------------|-----------------|------------------|
| A-5310 2-Stage Cyl. | 1860 | 2480 | 3100 |
| A-5461 3-Stage Cyl. | 2766 | 3688 | 4610 |
| A-5612 4-Stage Cyl. | 3672 | 4896 | 6120 |
| *A-5302 2-Stage Cyl. | 1812 | 2416 | 3020 |
| *A-5453 3-Stage Cyl. | 2718 | 3624 | 4530 |
| *A-5604 4-Stage Cyl. | 3624 | 4832 | 6040 |

*Includes adjustable down stop/anti-rotate mechanism.

